

SKU NUMBER#: 662187524511

CLARA BACK-LIT LED PANEL LIGHT (1'X4')
 (FIXED CCT & POWER)

POWER: 40 W | CCT: 3500 K
Product Description:

The RLUX CLARA HIGH EFFICACY BACK-LIT LED panel light is designed to offer a superior efficacy of 140 lm/W. It is an excellent alternative to the traditional fluorescent troffers. The thin and light-weight back-lit design easily lays into drop ceilings.


Features:

- Ultra Slim body.
- 140 lm/W, DLC Premium.
- UGR < 19 Flicker Free.
- UV Treated PS diffuser for Anti yellow with time.
- Inputs voltage range: 110 - 277 V, 50 - 60 Hz.
- CCT : 3500 K.
- Foldable edge design, no light leakage and better dust proofing.
- Fixed CCT & Power.
- Dimming and Sensor option available.

Ordering Information

Part Number	Fixture Type	Dimming	Wattage	CCT	Voltage	CRI	Internal
7	XX	D	YYYYW	CC	L	XX	Y

Series Code

Model Number	Wattage	CCT Optional	CRI	Efficacy	Diffuser Type
703D0040WCCLXXY	40 W	3500 K	80+	140 lm/W	PC (Frosted)

Fixture Details
Electrical

Power	40 W
Voltage	110 - 277 V
Current	0.3344 A
Power Factor	> 0.95
Total Harmonic Distortion (THD)	11.6%

Lighting Performance

Lumens	5600 lm
Efficacy	140 lm/W
Color Temperature (CCT)	3500 K
Color Rendering (CRI)	80+
Beam Angle	114.2°
Light Distribution	Type VS
Dimmable Lighting Control	0 - 10 V DC

LifeSpan

Average Life (Hours)	100000
Warranty (Years)	5

Construction

Housing	Aluminum Frame
Size	1' X 4'
Base / Power Supply	Hard Wired
Finish	White
Heat Sink Type	Back Plate
Optics Material / Lens	PC (Frosted)
Diffuser	PC (Frosted)
Number of LEDs	72

Components

LED Light Source	BRIDGELUX / CREE 2835, 1W
Driver	UL Approved Make

Environment

Operating Temperature	-14° F to +113° F
Ingress Protection Rating (IP)	IP20


Fixture Dimension (inch)

Length	47.83
Width	12
Height	1.77
Net Weight (lbs)	5.73
Gross Weight (lbs)	28.66

Packaging Dimension

Box Dimensions (inch)	49.4 x 7.87 x 14.96
Box Weight (lbs)	3.85
Quantity Per Box	4

Optometric Data




Qualifications

Model Number	703D0040WCCLXXY
SKU Number	662187524511



DesignLights Consortium® (DLC) Premium qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

Front view



Fixed

Wattage	CCT (Kelvin - K)	Efficacy (lm/W)	Lumen Output
40 W	3500 K	126.43	5057.2

Mounting Brackets

662187525242	Surface Mount Kit	1
662187525716	Microwave (PIR) Sensor	1