

TECHNICAL DATA SHEET

SKU NUMBER#: 662187525785 **VIGOROUS** LED SPORTS LIGHT POWER: 300 W | CCT: 4000 K | COLOR: Black

Product Description:

Rlux Vigorous LED Sports Light is made of aluminum alloy composition and has a rugged die-cast design with integrated cooling fans, all of which ensure optimum heat dissipation. The product supports a multi-faceted optic design which not only helps distribute light evenly but also reduces glare. With seamless link of aerometal materials and numerous vents on the heat sink, Vigorous offers improved heat management and a stable light system, making it a perfect choice for all kinds of outdoor stadiums.

Features:

- Superior aesthetics with a modern look.
- Excellent heat management system courtesy of multiple vents.
- 240° adjustable angle.
- Multi-faceted optic design to distribute light evenly and reduce glare.
- Inputs voltage range: 100 277 / 277 480 V, 50 60 Hz.

Ordering Information

Part Number	Fixture Type	Dimming	Wattage	CCT	Voltage	CRI	Light Distribution	Internal
50	XX	D	YYYYW	С	V	R	Х	Y

Series Code

Model Number	Wattage	CCT Optional	CRI	Efficacy	Lens Type
5001D0300WCVRXY	300 W	4000 K	80+	157.1 lm/W	PC Lens

Fixture Details

Electrical	
Power	300 W
Voltage	277-480 V
Current	0.625 A
Power Factor	0.995
Total Harmonic Distortion (THD)	8.8%
Surge Protection	6 kV

Construction

Die-cast Aluminum
PC Lens
Sosen
Black
1.59 ft ²
704
127.5 mph

Lighting	Performance
Lumens	

Lumens	47130 lm
Efficacy	157.1 lm/W
Color Temperature (CCT)	4000 K
Color Rendering (CRI)	72.6
Beam Angle	30°
Light Distribution	Type VS
PCB Thickness	0.6 mm
Typical LED Lumen	140 lm
Dimmable Lighting Control	Continuous Dimming to 10% or Below

Components

LED Light Source	LUMILEDS
Driver	Sosen

Environment

(+1 (317)-853-9650

Operating Temperature	-22 °F ~ +122 °F
Ingress Protection Rating (IP)	IP66
Impact Protection Rating	IK10

info@rlux.in

LifeSpan

Average Life (Hours)	1,00,000
Warranty (Years)	5

Industrial Lighting

RLUX reserves the right to discontinue products or to change the technical and/or design specifications at any time.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

www.rlux.in



<u>Rlux</u>

TECHNICAL DATA SHEET	TECHN	ICAL	DATA	SHEET
-----------------------------	-------	------	------	-------

Fixture Dimension	
Width (Inches)	16.33"
Height (Inches)	19.65"
Diameter (Inches)	15.94"
Net Weight (Ibs)	27.55


Qualifications

Model Number

SKU Number


5001D0300WCVRXY 662187525785

Optometric Data



Packaging Dimension

Box Dimensions (Inches)	17.71" x 17.71" x 13.97"
Box Weight (Ibs)	31.96
Quantity Per Box	1



Accessories

Shield
Yoke Mount Kit
Slip Fitter Mounting Bracket
Laser Aiming Device
Synapse-Wireless Control System

Industrial Lighting

🕻 +1 (317)-853-9650 | 🔗 info@rlux.in | 🌐 www.rlux.in