

SKU NUMBER#: 662187525914

# VIGOROUS LED SPORTS LIGHT

**POWER: 500 W | CCT: 4000 K | COLOR: Black**


## Product Description:

Rlux Vigorous LED Sports Light is made of aluminum alloy composition and has a rugged die-cast design with integrated cooling fans, all of which ensure optimum heat dissipation. The product supports a multi-faceted optic design which not only helps distribute light evenly but also reduces glare. With seamless link of aerometal materials and numerous vents on the heat sink, Vigorous offers improved heat management and a stable light system, making it a perfect choice for all kinds of outdoor stadiums.

## Features:

- Superior aesthetics with a modern look.
- Excellent heat management system courtesy of multiple vents.
- 240° adjustable angle.
- Multi-faceted optic design to distribute light evenly and reduce glare.
- Inputs voltage range: 100 - 277 / 277 - 480 V, 50 - 60 Hz.

## Ordering Information

Part Number	Fixture Type	Dimming	Wattage	CCT	Voltage	CRI	Light Distribution	Internal
50	XX	D	YYYYW	C	V	R	X	Y

### Series Code

Model Number	Wattage	CCT Optional	CRI	Efficacy	Lens Type
5001D0500WCVRXY	500 W	4000 K	80+	152.4 lm/W	PC Lens

## Fixture Details

### Electrical

Power	495.6 W
Voltage	100-277 V
Current	4.16 A
Power Factor	0.952
Total Harmonic Distortion (THD)	9.9%
Surge Protection	6 kV

### Construction

Housing	Die-cast Aluminum
Cover Material / Lens	PC Lens
Base / Power Supply	Sosen
Finish	Black
Effective Projected Area (EPA)	1.59 ft <sup>2</sup>
Number of LEDs	704
Wind Shear Rating	127.5 mph

### LifeSpan

Average Life (Hours)	1,00,000
Warranty (Years)	5

### Lighting Performance

Lumens	75529.44 lm
Efficacy	152.4 lm/W
Color Temperature (CCT)	4000 K
Color Rendering (CRI)	73.5
Beam Angle	30°
Light Distribution	Type I, Very Short
PCB Thickness	0.6 mm
Typical LED Lumen	140 lm
Dimmable Lighting Control	Continuous Dimming to 10% or Below

### Components

LED Light Source	LUMILEDS
Driver	Sosen

### Environment


Operating Temperature	-22 °F ~ +122 °F
Ingress Protection Rating (IP)	IP66
Impact Protection Rating	IK10

**Fixture Dimension**


Width (Inches)	16.33"
Height (Inches)	19.65"
Diameter (Inches)	15.94"
Net Weight (lbs)	27.55

**Packaging Dimension**

Box Dimensions (Inches)	17.71" x 17.71" x 13.97"
Box Weight (lbs)	31.96
Quantity Per Box	1


**Qualifications**

Model Number	5001D0500WCVRXY
SKU Number	662187525914


**Optometric Data**
**500 W**

**Accessories**

INCLUDE IN THE BOX

662187526065	Shield
662187526072	Yoke Mount Kit

SOLD SEPARATELY

662187526089	Slip Fitter Mounting Bracket
662187526096	Laser Aiming Device
662187526102	Synapse-Wireless Control System