

TECHNICAL DATA SHEET

SKU NUMBER#: 662187526027 VIGOROUS LED SPORTS LIGHT POWER: 600 W | CCT: 4000 K | COLOR: Black

Product Description:

Rlux Vigorous LED Sports Light is made of aluminum alloy composition and has a rugged die-cast design with integrated cooling fans, all of which ensure optimum heat dissipation. The product supports a multi-faceted optic design which not only helps distribute light evenly but also reduces glare. With seamless link of aerometal materials and numerous vents on the heat sink, Vigorous offers improved heat management and a stable light system, making it a

Features:

• Superior aesthetics with a modern look.

perfect choice for all kinds of outdoor stadiums.

- Excellent heat management system courtesy of multiple vents.
- 240° adjustable angle.
- Multi-faceted optic design to distribute light evenly and reduce glare.
- Inputs voltage range: 100 277 / 277 480 V, 50 60 Hz.

Ordering Information

Part Number	Fixture Type	Dimming	Wattage	CCT	Voltage	CRI	Light Distribution	Internal
50	XX	D	YYYYW	С	V	R	Х	Y

Series Code

Model Number	Wattage	CCT Optional	CRI	Efficacy	Lens Type
5001D0600WCVRXY	600 W	4000 K	80+	143.1 lm/W	PC Lens

Fixture Details

Electrical	
Power	600 W
Voltage	100-277 V
Current	5 A
Power Factor	0.999
Total Harmonic Distortion (THD)	8.9%
Surge Protection	6 kV
Construction	
Housing	Die-cast Aluminum
Cover Material / Lens	PC Lens
Base / Power Supply	Sosen

Lighting Performance

<u> </u>	
Lumens	85860 lm
Efficacy	143.1 lm/W
Color Temperature (CCT)	4000 K
Color Rendering (CRI)	73.1
Beam Angle	30°
Light Distribution	Type I, Very Short
PCB Thickness	0.6 mm
Typical LED Lumen	140 lm
Dimmable Lighting Control	Continuous Dimming to 10% or Below

Components

LED Light Source	LUMILEDS
Driver	Sosen

Environment

(+1 (317)-853-9650

Operating Temperature	-22 °F ~ +122 °F
Ingress Protection Rating (IP)	IP66
Impact Protection Rating	IK10

info@rlux.in

LifeSpan

Number of LEDs

Wind Shear Rating

Finish

Average Life (Hours)	1,00,000
Warranty (Years)	5

Industrial Lighting

Effective Projected Area (EPA)

RLUX reserves the right to discontinue products or to change the technical and/or design specifications at any time.

Black

704

1.59 ft²

127.5 mph

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

www.rlux.in



Rlux

	TECHNICAL	_ DATA	SHEET
--	------------------	--------	-------

Fixture Dimension	
Width (Inches)	16.33"
Height (Inches)	19.65"
Diameter (Inches)	15.94"
Net Weight (lbs)	27.55

Packaging Dimension

Box Dimensions (Inches)

Box Weight (lbs)

Quantity Per Box

Qualifications


Model Number


SKU Number


5001D0600WCVRXY 662187526027

90°

Optometric Data







Accessories UDE IN THE BOX

INCLUDE IN THE BOX	
662187526065	Shield
662187526072	Yoke Mount Kit
SOLD SEPARATELY	
662187526089	Slip Fitter Mounting Bracket
662187526096	Laser Aiming Device
662187526102	Synapse-Wireless Control System

Industrial Lighting

@ www.rlux.in **L** +1 (317)-853-9650 info@rlux.in

RLUX reserves the right to discontinue products or to change the technical and/or design specifications at any time. The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.