Rlux

ITEM #: 662187518503


Mono Crystalline Solar Panel - 50W

FEATURES

- High conversion efficiency: Greatly reduces light and electricity loss.
 Leading in component power industry
- Strong stability: effectively enhance the reliability and stability
- Significantly reduce the effect of hot spot
- 10-year warranty on material and workmanship, 25-year warranty on linear power output
- Reduce system cost: high component efficiency can effectively reduce the floor space, BOS, transportation, and operation costs by 5-10%

APPLICATIONS

• The solar panel is able to charge the batteries of the vehicles such as boat, motorhome, caravan, camper, narrowboat, and yacht, etc, or any other system with a 12V battery or battery bank.



PRODUCT DETAILS

ELECTRICAL


LEEOTRIOAL	
Max Power	50W
Open Circuit Voltage	21.8V
Voltage at Pmax	18.24V
Short-Circuit Current	2.97A
Current at Pmax	2.74A
Cell efficiency (%)	23%
Power Tolerance	<u>+</u> 0.5%
Power Temp Coefficient	-0.47% / °C
Voltage Temp Coefficient	-0.38% / °C
Current Temp Coefficient	0.04% / °C
Output Power Tolerence	±03%
Normal Operation Condition Test	47 <u>+</u> 2°C

Module

Solar Cell Brand	MONO Crystalline Silicon	
Solar Cell Qty.	2X16pcs	
Module Dimension	(26.3X15.7X0.98) inch	
Connector	MC 4	
Waterproof Junction Box	IP65/IP67	

DIMENSIONS	(Inches)	(mm)
Length	26.3	670
Width	15.7	400
Height	0.98	25





Rohs (E

www.rlux.in | +1 317-853-9650

© 2022 Rlux. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.